



Rated Power : 131 kW
Teeth Weight : 1709 Kg
Blade Capacity : 4.5m³
Operating Weight : 17100 Kg

XG4161L BULLDOZER

TRUSTED EVERYWHERE



Photos may include optional equipment



Head Office
Kawasan Industri & Pergudangan Marunda Center
Blok A2 No. 10, Jl. Marunda Makmur, Segara Makmur, Tarumajaya
Kab. Bekasi, Jawa Barat
Indonesia 17211
☎ : (+62-21) 2214 8087, 2214 8889
Hot Sales :

info@dayasakti.net | www.dayasakti.net

Excellent Performance

- ◆ Equipped with the Cummins Turbocharged engine for powertrain, which matches well with the hydraulic converter, enjoys a wide speed range in the high - efficiency area and manages to achieving the optimum output power by changing its torque automatically according to the ground resistance within a certain range and working with the power gearshift transmission, thus meeting various working conditions.
- ◆ Equipped with a hydraulic drive system with hydraulic control technology and an advanced structure, which provides reliable performance and convenient and flexible operation.
- ◆ The hexahedral operator cabin provides the operator with quiet and ergonomic operating environment with all around visibility reducing blind spot.
- ◆ Equipped with straight-tilting shovel as standard as well as U shovel and angle shovel as options, all provided with well durable blade.
- ◆ Optiona equipped with the ripper, 3-tooth or 1-tooth available.



Technical Specification

Model	XG4161L
Engine Model	Weichai WD10G178E25
Rated power (kW)	131
Rated rpm (r/min)	1850
Blade height (mm)	1168
Blade width (mm)	3416
Max. depth (mm)	545
Max. lift (mm)	1095
Max. tilt adjustment (mm)	≥400
Pitch adjustment (°)	55
Min. ground clearance (mm)	400
Ground pressure (Mpa)	0.069
Min. turning radius (mm)	3100
Grade ability (°)	30
Blade capacity (m³)	4.5
Productivity (m³/h)	270
Fuel consumption (g/kW.h)	223

Travel speed (km/h)	FORWARD 1ST	0 ~ 3.8
	FORWARD 2ND	0 ~ 6.6
	FORWARD 3RD	0 ~ 10.6
	REVERSE 1ST	0 ~ 4.9
	REVERSE 2ND	0 ~ 8.5
	REVERSE 3RD	0 ~ 13.6
Teeth		3
Max. digging depth (mm)		572
Max. lift (mm)		702
Teeth weight (kg)		1709
Basic operating weight (kg)		17100
Basic dimension (LxWxH)		5188x3416x3060
With rippers and ROPS dimension (LxWxH)		6215x3416x3060

BRANCH OFFICE

Semarang | Surabaya | Medan | Pekanbaru | Palembang
Balikpapan | Samarinda | Banjarmasin | Makassar