



Rated Power : 162 kW
Operating Weight : 23450 Kg
Blade Capacity : 6.4m³
Teeth Weight : 3600 Kg (1 teeth)
2900 Kg (3 teeth)

XG4221L

BULLDOZER

**TRUSTED
EVERYWHERE**



Photos may include optional equipment



Head Office

Kawasan Industri & Pergudangan Marunda Center
Blok A2 No. 10, Jl. Marunda Makmur, Segara Makmur, Tarumajaya
Kab. Bekasi, Jawa Barat
Indonesia 17211

☎ : (+62-21) 2214 8087, 2214 8889

Hot Sales :

info@dayasakti.net | www.dayasakti.net

Excellent Performance

- ◆ Equipped with the Cummins Turbocharged engine for powertrain, which matches well with the hydraulic converter, enjoys a wide speed range in the high - efficiency area and manages to achieving the optimum output power by changing its torque automatically according to the ground resistance within a certain range and working with the power gearshift transmission, thus meeting various working conditions.
- ◆ Equipped with a hydraulic drive system with hydraulic control technology and an advanced structure, which provides reliable performance and convenient and flexible operation.
- ◆ The hexahedral operator cabin provides the operator with quiet and ergonomic operating environment with all around visibility reducing blind spot.
- ◆ Equipped with straight-tilting shovel as standard as well as U shovel and angle shovel as options, all provided with well durable blade.
- ◆ Optiona equipped with the ripper, 3-tooth or 1-tooth available.



Technical Specification

Model	XG4221L
Engine Model	Cummins NT855 - C280
Rated power (kW)	162
Rated rpm (r/min)	1800
Blade height (mm)	1315
Blade width (mm)	3725
Max. depth (mm)	540
Max. lift (mm)	1210
Max. tilt adjustment (mm)	≥735
Pitch adjustment (°)	55
Min. ground clearance (mm)	405
Ground pressure (Mpa)	0.077
Min. turning radius (mm)	3300
Grade ability (°)	30
Blade capacity (m³)	6.4
Productivity (m³/h)	330
Fuel consumption (g/kW.h)	212

Travel speed (km/h)	FORWARD 1ST	0 ~ 3.6
	FORWARD 2ND	0 ~ 6.5
	FORWARD 3RD	0 ~ 11.2
	REVERSE 1ST	0 ~ 4.3
	REVERSE 2ND	0 ~ 7.7
	REVERSE 3RD	0 ~ 13.2
Teeth	1 or 3 tooth	
Max. digging depth (mm)	1 tooth	690
Max. digging depth (mm)	3 tooth	665
Max. lift (mm)	1 tooth	533
Max. lift (mm)	3 tooth	555
Teeth weight (kg)	1 tooth	3600
Teeth weight (kg)	3 tooth	2900
Operation weight (kg)	23450	
Dimension (LxWxH) (mm)	5530x3725x3325	
With ripper and ROPS dimension (LxWxH) (mm)	6793x3725x3400	

BRANCH OFFICE

Semarang | Surabaya | Medan | Pekanbaru | Palembang
Balikpapan | Samarinda | Banjarmasin | Makassar