



Rated Power : 162 kW
Rated Load : 5000kg
Bucket Capacity : 3.0 m3
Operating Weight : 17200 kg

XG955N

Wheel Loader

**TRUSTED
EVERYWHERE**



Head Office

Kawasan Industri & Pergudangan Marunda Center
Jl. Marunda Makmur Blok A2 No. 10, Jawa Barat 17211

☎ (+62-21) 2214 8889 / 2214 8087

www.dayasakti.net

Key Features

- Powerful, flexible and highly efficient
- Easily operated safe and comfortable
- An optimized structure for stability and reliability
- Convenient maintenance and easy care



Technical Specification

Model	XG955N	Max. Travel Speed - Reverse (km/h)	16
Engine Manufacturer	Sangchai	Tyre size	23.5-25-16PR
Engine Model	SC11CB220G2B1	Steering Angle (both left and right) (°)	35
Rated power (Kw)	162	Min. turn radius (mm)	5775
Rated speed (r/min)	2200	Min. turn radius outside bucket (mm)	6650
Max torque (N.m)	844	Overall Length (mm)	A 7740
Rated load (kg)	5000	Overall width (mm)	B 3000
Bucket Capacity (m ³)	3.0	Overall height (mm)	C 3450
Operating weight (kg)	17200	Wheel base (mm)	D 2880
Gradeability (°)	25	Thread width (mm)	E 2240
Max. turning angle (°)	±35	Ground clearance (mm)	F 500
Max. breakout force (KN)	>180	Bucket width (mm)	G 3000
Maximum traction (KN)	165	Max. dumping height (mm)	H 3220
Hydraulic cycle time, raise (s)	<5.8	Max. Operating Height (mm)	I 5520
Hydraulic cycle time, total (s)	11	Hinge pin height (mm)	J 4120
Gearbox	XGMA	Dumping reach (mm)	K 1185
Axle	XGMA	Fuel tank (ltr)	220
No of Speed	2F/1R	Hydraulic tank (ltr)	295
Max. Travel Speed - Forward (km/h)	40	Hydraulic System Pressure (MPa)	16

BRANCH OFFICE

Jakarta | Tangerang | Pekanbaru | Medan | Palembang | Balikpapan |
Pontianak | Makassar | Semarang | Surabaya | Denpasar